

SoloMaxx Revolution SLT

GENERAL LINK



動作電圧：DC3.3V~4.2V
動作電流：<150mA
周波数：2400~2483MHz
FMRレート：250kbps
チャンネル数：6ch
動作可能時間：約2時間

※下記参考値はあくまで設定例です。お客様のお好みに合わせ変更して下さい。

		Transmitter:Hitec Aurora 9					
	1	2	3	4	5	6	7
Channel	NOR	NOR	NOR	NOR	NOR	NOR	NOR
E Curve	0	0		0			
Throttle Curve	0	40	60	68	73	85	100
3D Throttle Curve	100	100	100	100	100	100	100
General Pitch Curve	27	44	50	55	60	68	85
3D Pitch Curve	20	36	42	50	60	75	90
Gyro Sensitivity	75			Swashplate	1 servo(90°)		

		Transmitter:FUTABA T6J					
	1	2	3	4	5	6	7
Channel	NOR	NOR	NOR	NOR	NOR	NOR	NOR
E Curve	10	10		0			
Throttle Curve	0	55	75	85	100		
3D Throttle Curve	100	95	90	95	100		
General Pitch Curve	27	42	55	65	68		
3D Pitch Curve	20	39	50	60	70		
Gyro Sensitivity	75			Swashplate	H-1		

		Transmitter:JR XG8					
	1	2	3	4	5	6	7
Channel	NOR	NOR	NOR	NOR	NOR	NOR	NOR
E Curve	20	20		0			
Throttle Curve	0	40	75	85	100		
3D Throttle Curve	100	95	90	95	100		
General Pitch Curve	27	42	55	65	68		
3D Pitch Curve	17	39	50	60	70		
Gyro Sensitivity	75			Swashplate	1S Normal		

		Transmitter:WALKERA DEVO-8S					
	1	2	3	4	5	6	7
Channel	NOR	NOR	NOR	NOR	NOR	NOR	NOR
E Curve	straight line	straight line		straight line			
Throttle Curve	0	16.5	33.5	50	66.5	83.5	100
3D Throttle Curve	100	100	100	100	100	100	100
General Pitch Curve	-43	forbidden	-8	6	33	forbidden	40
3D Pitch Curve	-61	forbidden	-22	3	33	forbidden	45
Gyro Sensitivity	87.5 / 79.5			Swashplate	1Servo Normal		

		Transmitter:SPEKTRUM DX8					
	1	2	3	4	5	6	7
Channel	NOR	NOR	NOR	NOR	NOR	NOR	NOR
E Curve							
Throttle Curve	0	55	71	85	100		
3D Throttle Curve	100	95	90	95	100		
General Pitch Curve	40	45	55	65	75		
3D Pitch Curve	20	35	52	65	80		
Gyro Sensitivity	75			Swashplate	1Servo Normal		